


## BOOOI ACE Series

Classic Model | Single Platform Metal Sheet Laser Cutting Machine with Full Enclosure





### Full Enclosure Zero Worries for Safety


Equipped with a complete safety light curtain and fully enclosed crossbeam protection, the machine ensures operator safety and complies with international safety standards.






# Cutting Parameter AutoMatch

Through visual comparison of sample parts and cutting parameter automatch to enhance cutting quality, and reduce labor costs.







Comprehensive performance

### improved by 20 %

relative to the last generation.


bodor

### Maximum acceleration up to 2 C

It adopts high-performance bus servo motors to achieve the absolute leading dynamic performance (compared with similar products in the market).

Significantly improving processing efficiency to ensure that every second you invest is creating value.







#### Sheet Edge Anti-vibrating Stable Cutting

Through the powerful algorithm, it is able to adapt to the high frequency vibration of thin plate due to air pressure. The laser head sensitivity is intelligently adjusted, ensuring consistently stable cutting, thereby guaranteeing both cutting quality and efficiency.









#### 5-year Warranty for Bodor Self-developed Three Core Laser Components

With our perfect integration technology for the self-developed BodorThinker control system, BodorPower laser source, and BodorGenius laser head, we can extend the service warranty for these three core components to five years! The three core components are designed, produced, tested, and delivered in an integrated manner, working perfectly together to make the equipment run more stably and efficiently. At the same time, it greatly reduces the risk of component contamination and failure rate, extends the lifespan, and lowers maintenance costs by avoiding repeated assembly.



Control System

Laser Source


Laser Head





#### A Series Parameters

	A3 CE
Working Area	3048mm×1524mm
Max. Linkage Speed	80m/min
Max. Accelaration	1.2 G
Lightning Perforation	
Remnant Typesetting	
Active Anti-Collision Function	
Intellgent Over-Heat Adaptation	×
Intelligent Anti-Shake	
Auto-Focus of Laser Head	
Cutting Parameter AutoMatch	





### bodor No.